

CAPACITORS


CALL FOR AVAILABILITY

CAPACITORS

HIGH CURRENT CAPACITOR

AEROVOX #AFPS. Rated 3 mfd @ 450 VDC. Metalized Polypropylene dielectric tape construction, with epoxy filled end caps. Tolerance: $\pm 10\%$. Ideal for applications where large peak and rms currents are encountered, such as switch mode power supplies, inverters, welders, and electronic ballasts. Radial leads are 3/4" long. Dimensions: 15/16" wide x 1-3/8" long (excluding leads).

Stock #CAP2308



\$2.00 ea.
10 for \$15.00

ENERGY STORAGE CAPACITOR

AEROVOX, #ZR112YW106P01. Rated at 106 MFD, 1150 VDC peak. These are designed for stored energy pulse applications. Please note: Supplied with a shorting strap installed. Use caution! Stored energy levels of this device are lethal. Has insulated, shrouded, 1/4" quick tab connections. Dimensions: 2-9/16" dia. x 5-1/4" high.

Stock #CAP2303



ENERGY STORAGE CAPACITOR

CORNELL DUBILIER #NRG203. 10.0 MFD 20 KVDC. Single terminal. 2000 joules. Dimensions: 2 1/2" high x 7-1/2" thick x 14" wide. UPS.


Stock #CAP9859



ENERGY STORAGE CAPACITOR

TOBE, #E5C 248A. 15 MFD 20,000 VDC 3000 JOULES. Single terminal. Dimensions: 27" high x 14" wide x 7-3/8" thick. Weight: 150 lbs. Ship freight. No PCB's.

Stock #CAP99519



ENERGY DISCHARGE CAPACITOR

AEROVOX or G.E. Nominal capacitance rating 88 MFD. 1200 VDC. Dimensions: 10-1/2" high x 4-5/8" wide x 3-7/8" deep.

Stock #CAP9311

ELECTROLYTIC CAPACITORS

MFD	VOLTAGE	MFR	NO.	LENGTH	DIA.	STOCK NO.
150	400VDC	MALLORY	CG151T400R4C	4-1/2"	1-3/8"	CAP9918
500	320VDC	SPRAGUE	D36783	3-1/4"	1-3/4"	CAP0876
560	400VDC	CEU-P (COMPUTER GRADE)		3-1/2"	1-3/4"	CAP21512
600	175VDC	INDUSTRIAL CONDENSER	312699	4-7/8"	1-3/8"	CAP2301
TOL. -10+50%						
820	450VDC	MALLORY	CGS821T450W3L3PL	3-3/4"	2-1/2"	CAP9908
900	85VDC	SANGAMO	DCM	3-5/8"	1-3/8"	CAP91542
1000	450VDC	TOSHIBA/MARCON	CECW P2 W102 M2-L22	3-1/8"	2"	CAP9706
1000	150VDC	MALLORY	HC15010	4-1/2"	2-1/16"	CAP9411
1200	400VDC	SPRAGUE	32D5551	6-1/8"	3-1/16"	CAP9101
1200	200VDC	MEPCO/ELECTRA	3186	6"	1-3/8"	CAP0889
1400	200VDC	SPRAGUE		4-1/4"	2"	CAP8854
1400	450VDC	CAPACITOR TECH. "FAO"	FA0142F450E1L	5-3/4"	3-1/2"	CAP21513
1500	300VDC	MALLORY	HES	4 1/2"	2-1/2"	CAP8855
1800	200VDC	CDE	500-1093-01	6"	2"	CAP9452
1800	350VDC	CORNELL/DUBILIER	36DX9483	5-1/2"	3"	CAP2500
1800	450VDC	SPRAGUE		4-1/4"	2"	CAP8854
1900	40VDC	SPRAGUE	32D1123	4-1/2"	1-3/8"	CAP9855
2100	400VDC	AEROVOX	CGS 12-712412-00	5-1/2"	3-1/16"	CAP9951
475VDC SURGE						
2600	100VDC	MALLORY	CGS262	4-1/8"	1-3/8"	CAP9001
2700	40VDC	MALLORY	CGS272U040L	2-1/4"	1-3/8"	CAP9919
2700	400VDC	HATACHI	HCGFAR	6-1/2"	2-1/2"	CAP21514
450VDC SURGE						
3000	50VDC	GENERAL ELECTRIC	86F886M	4-1/2"	1-3/4"	CAP0786
3100	75VDC	MALLORY	CGS312	4-1/8"	1-3/8"	CAP9002
3100	450VDC	SPRAGUE	36DX	9-1/4"	3"	CAP2304 *RF
3300	150VDC	PHILLIPS	3186BN332M150APAZ	6"	1-13/32"	CAP9759
3300	400VDC	MARCON		8"	3"	CAP2406 *RF
3700	50VDC	MEPCO/ELECTRA	86F4877M	4-1/2"	1-3/8"	CAP0865
3900	75VDC	GENERAL ELECTRIC	86F2128M	3-3/8"	2"	CAP0858
4000	40VDC	MEPCO/ELECTRA	86F156MI	3-1/4"	1-3/8"	CAP9106
4100	300VDC	MALLORY	CGS	6"	3"	CAP2200 *RF
4200	50VDC	MEPCO/ELECTRA	3186BE422	4-1/8"	1-3/8"	CAP9206
4800	130VDC	PHILLIPS	3186DE482U130AMA2	4-3/8"	1-3/4"	CAP2305
175 SURGE						
5000	50VDC	MEPCO/ELECTRA	43F4110MA4	4-1/4"	2"	CAP9453
5200	30VDC	MEPCO/ELECTRA	86F147M	3-1/2"	1-3/8"	CAP0860
5500	200VDC	SPRAGUE	36D	5-3/4"	3"	CAP2001
5600	40VDC	MEPCO/ELECTRA	3120	2-1/4"	2"	CAP0887
6000	300VDC	MALLORY	CGS602T300X8L	9"	3"	CAP9955
6200	250VDC	CORNELL DUBILIER	500X622T250DF2B	5-5/8"	3"	CAP20517
6800	400VDC	HATACHI	HCGFAR	6-1/2"	3-1/2"	CAP21516
450VDC SURGE						
7400	30VDC	MALLORY	CGS	3-1/2"	1-3/8"	CAP9920
7500	350VDC	CORNELL DUBILIER	DCM752T350DP2BS	6"	3"	CAP20518
7800	100VDC	SANGAMO	DCM782T100DC2A	4-1/2"	3"	CAP2050
8000	100VDC	CORNELL DUBILIER	500802T100DD2B	5"	3"	CAP2002
9000	50VDC	SPRAGUE	36D	2"	4-1/4"	CAP91515
9600	75VDC	MALLORY	CGR	4-1/8"	2-1/2"	CAP2157
10,000	50VDC	MEPCO/CENTRALAB	3188GE1034050AMA	4-3/4"	3"	CAP2502
75 SURGE						
10,000	60VDC	PHILLIPS CAPACITOR	3186GP1034060AMAZ	4"	3"	CAP9852
11,000	30VDC	CAPACITOR TECH.	FA7113G030BEIL	4"	1-3/8"	CAP9856
12,000	250VDC	C-D	HR101X123U250DP2B	6-1/8"	3"	CAP2107
12,000	250VDC	CHEMI-CON	36DX	8-3/4"	3"	CAP2408 *RF
12,900	40VDC	MEPCO/ELECTRA	86F159M	4-1/2"	2"	CAP0862
14,000	30VDC	SPRAGUE	36D	2"	4-1/4"	CAP91512
15,000	50VDC	SPRAGUE	CE71C153G	5-3/4"	2-1/2"	CAP9352
16,000	60VDC	NIPPON	KS2000133L9	5-1/2"	3"	CAP97510
16,500	50VDC	MALLORY	CG	5-5/8"	3"	CAP9051

Continued on next page

*REMOVED FROM EQUIPMENT

CAPACITORS

ELECTROLYTIC CAPACITORS (continued)

MFD	VOLTAGE	MFR	NO.	LENGTH	DIA.	STOCK NO.
17,000	30VDC	CAPACITOR TECH.	FA173G08GIL	4-5/8"	1-3/8"	CAP9854
18,000	30VDC	SPRAGUE	36DX	5-5/8"	1-3/8"	CAP9153
20,000	25VDC	MALLORY	CG2034025V4C	4-1/2"	2"	CAP2055
20,000	35VDC	MEPCO/ELECTRA	3186FC2034035AMA2	3-1/2"	2-1/2"	CAP2056
22,000	15VDC	SPRAGUE	CE71C223E	4-1/2"	2"	CAP9857
24,000	25VDC	CDE	FAH	2"	4-1/2"	CAP91510
27,000	30VDC	MEPCO/ELECTRA	86F	4-1/2"	2"	CAP0843
27,000	15VDC	MALLORY	CG273U015	3-3/8"	2"	CAP9113
30,000	50VDC	MALLORY	CGS303U050V5L	6"	2"	CAP9911
31,000	15VDC	SPRAGUE	36D	2"	4-1/4"	CAP9156
36,000	20VDC	MALLORY	CGS363U020R5C3PH	5-7/16"	1-3/8"	CAP9927
37,000	40VDC	SANGAMO	DCM373U040DD2B	5"	3"	CAP2057
44,000	100VDC	MALLORY	CGS or CAP. TECH. FAO TYPE 9"	9"	3"	CAP2405
50,000	15VDC	MALLORY	CGS503U015V4C3PL	4-1/4"	2"	CAP9917
54,000	20VDC	AEROVOX	CGS543U020-W4C3PH	4-1/4"	2-1/2"	CAP9304
56,000	15VDC	MALLORY	CGS	2"	4-1/4"	CAP9157
67,000	10VDC	MALLORY	CGS	3-1/2"	2"	CAP9154
82,000	16VDC	CAPACITOR TECH. "FAO"	FA0823G016F1L	4-3/8"	2"	CAP21517
83,000	15VDC	MEPCO/ELECTRA	3186FE	4-1/2"	2-1/2"	CAP9006
85,000	15VDC	COMPUTAMITE	CDE	4-1/2"	2-1/2"	CAP0842

10 for

OIL FILLED CAPACITORS

MFD	VOLTAGE	MFR. and NO.	LENGTH	WIDTH	HEIGHT	TERMS.	STOCK NO.
0.025	2800VAC 60HZ	G.E.	1-11/32"	2-3/16"	2-3/4"	Solder	CAP9956
0.015	5000VDC						
0.1	3000	HEC #CQ72E1GL104K1	2-1/2"	1-1/4"	3-1/4"	S	CAP9454
0.25	2000VAC	G.E. #343x788	3-3/4"	1-3/16"	2-5/8"	S	CAP2503
0.25	7.5KVA	HEC #CQ72D1GR254K3	4-5/8"	3-3/4"	5-5/8"	S	CAP9400
3X.66	1000VDC	BYCAP #2B102-195A	2-1/2"	1-1/4"	4"	Solder	CAP9404
0.5	1150Vp	RONKEN #86A85504K50B	2-3/16"	1-5/16"	2-3/4"	Q	CAP2103
0.95	1800VAC	G.E. #23L6335R	2-3/16"	1-3/8"	3-1/4"	Q	CAP9708
1	800VAC 60HZ	CAPTRON #957-262802	2-3/16"	1-5/16"	3-5/8"	Q	CAP2104
1	1KVDC	SPRAGUE #305-1030	1-3/4"	1"	3"	S	CAP0313
1	660VAC	G.E. #26F6127	2-1/8"	1-3/8"	2-5/8"	Q	CAP9554
1	1000VDC	G.E. #26F5521	2-1/8"	1-3/8"	3-3/8"	S	CAP95517
1	2500VAC	G.E. #23L6194, #23L6347	2-1/8"	1-3/8"	4-1/2"	Q	CAP95518
1.02	2100VAC	G.E. #26L6300R	2-1/8"	1-3/8"	4-1/2"	Q	CAP95519
1.4	3000VAC	G.E. #23L6378 (HAS INTERNAL RESISTOR)	3-3/4"	2"	7-1/4"	Q	CAP2300
2	660VAC	G.E. #26F1700	2-1/8"	1-3/8"	3-1/2"	Q	CAP9555
2	1.5KVDC	G.E. #23F371	2-1/2"	1-1/8"	4"	S	CAP0314
2	800VDC	G.E. #97F8678	2-1/8"	1-3/8"	4-3/4"	S	CAP95520
2	1200VAC 60HZ	G.E. #26F6969FA	3-1/2"	1-3/4"	3"	Q	CAP2150
2.03	570VAC	G.E. #21L219R	2-1/8"	7/8"	2-1/4"	Wire	CAP9556
2.4	2500VAC	G.E. #23L6372	3-1/2"	1-3/4"	7-3/4"	Q	CAP97525
2.5	370VAC	G.E. #21L6066	1-3/8"	2-1/8"	2-5/8"	Q	CAP0851
3	370VAC 60HZ	AEROVOX #P50G3703E05	2-3/16"	1-5/16"	2-11/16"	Q	CAP9954
3	370 VAC 60 HZ	DAYTON #4X425	2"	1-3/8"	2-1/2"	Q	CAP2400
3	370VAC	G.E. #21L6275	2-1/8"	1-1/4"	2-1/4"	Q	CAP9216
3	480VAC	MAGNETEK #VCO3048CATR	2"	1-1/4"	3-1/4"	Q	CAP97515
3	660VAC 50/60HZ	G.E. #61L1272	2-1/4"	1-3/8"	3-3/8"	Q	CAP2004
3	660VAC	G.E. #26F6404	2-3/16"	1-3/8"	4-3/4"	Q	CAP2401
3	660VAC	G.E. #26F1031	2-3/4"	1-5/8"	3-7/8"	Q	CAP2402
3.5	440VAC	G.E. #21L6027	2"	1-1/4"	2-3/4"	Q	CAP2159
3.75	370VAC	AEROVOX #P50G3703Y	2"	1-3/16"	2-5/8"	Q	CAP8851
4	370VAC	G.E. #297F5704	2-3/16"	1-3/16"	2-5/8"	Q	CAP2052
4	660VAC	G.E. or AEROVOX	2"	1-13/16"	4-3/4"	Q	CAP2158
4	1000VAC	RONKEN #86C32405H01	2-3/4"	1-3/4"	4-3/4"	Q	CAP97524

S=Screw Q=Quick Disconnect + 5/8" long mounting screw on bottom

Continued on next page

ELECTROLYTIC CAPACITOR

HITACHI, #HCG FAR. Rated 6800 MFD 400 VDC. The surge voltage is rated at 450 VDC. Has sturdy screw type mounting for electrical connections. A removable mounting clamp is included. Dimensions: 3-1/2" dia. x 7" long.

Stock #CAP21516



ELECTROLYTIC CAPACITOR HATACHI. 2700 UF

400 VDC. #HCG FAR. Surge voltage rating is 450 VDC. Has sturdy screw terminals on the top surface. Dimensions: 2-1/2" dia. x 6-1/2" long (including terminals).

Stock #CAP21514

ELECTROLYTIC CAPACITOR


NICHICON, #CE L Q (M). Printed circuit, snap-in mounting, electrolytic capacitor. Rated 680 MFD 400 VDC (working). The temperature rating is +85°C. The leads are 0.060" dia. (max.) x 3/16" nom. long. Dimensions: 1-3/8" dia. x 2" long (excluding leads).

Stock #CAP21511

ELECTROLYTIC CAPACITOR

JIANGHAI #CD 294. Rated 560 MFD, 400 VDC. Printed circuit mount. Dims: 1-3/8" diameter x 2-5/16" long, including terminal pins on the bottom.

Stock #CAP2501



ELECTROLYTIC CAPACITOR

CORNELL DUBILIER, #DCM752T350DP2BS. Rated 7,500 MFD 350 VDC. The negative terminal of this capacitor is a large male threaded stud located at the end of the unit, opposite the top terminals. The stud is threaded 11.25mm x 1.75mm pitch. The stud is 5/8" long. The top of the capacitor has two tapped connection posts. One of the posts is the positive connection and the other one is not connected to anything. Dimensions: 3" dia. x 6" long (excluding the end stud).

Stock #CAP20518

ELECTROLYTIC CAPACITOR

SPRAGUE, #80D153P025KE5D. Printed circuit mount electrolytic capacitor. Rated 15000 MFD. 25 VDC, 30 VDC surge. Temperature rating 85°C max. Dimensions: 1-3/8" dia. x 1-5/8" high. The mounting pins/terminals extend 1/4 beyond the base.

Stock #CAP2214




CAPACITORS CALL FOR AVAILABILITY

CAPACITORS

ELECTROLYTIC CAPACITOR

MALLORY, Type CGS. Rated 67,000 MFD 10 VDC The surge voltage rating is 12 VDC. Has sturdy screw type terminals for electrical connections. Dimensions: 2" dia. x 3-1/2" long.
Stock #CAP9154



ELECTROLYTIC CAPACITOR

TOSHIBA/MARCON, #CECWP2W102M2-L22. Rated 1000 MFD 450 VDC +85°C maximum temperature. Sturdy screw type mounting for electrical connections. Has removable mounting clamp. Dimensions: 2" dia. x 3-1/8" long.
Stock #CAP9706



METALIZED POLYPROPYLENE CAPACITOR

ELECTRONICS CONCEPTS, #5MP16. 10.0 MFD ±10% 400 VDC. These capacitors were designed for low ESR, high current, high capacitance applications such as switching power supplies. Ideal for all applications requiring low ESR capacitors. Capacitor has metal tabs at each end for connections. The tabs are 7/16" long and have a hole that will accept a No. 6 screw. Dimensions: 1-9/16" dia. x 2-3/8" long (excluding tab connections).
Stock #CAP9958



METALIZED POLYPROPYLENE CAPACITOR

ELECTRONICS CONCEPTS, #EC 5MP-11372K. 10 MFD ±10% 450 VDC. These capacitors were designed for low ESR, high current, high capacitance applications such as switching power supplies. Ideal for all applications requiring low ESR capacitors. Capacitor has metal tabs at each end for connections. The tabs are 7/16" long and have a hole that will accept a No. 6 screw. Dimensions: 1-9/16" dia. x 2-3/8" long (excluding tab connections).
Stock #CAP97513

METALIZED POLYCARBONATE CAPACITOR

ELECTROCUBE, #625B1C106K. 10.0 MFD ±10% 200 VDC. Metalized Polycarbonate dielectric. Capacitor has axial leads which are 2-5/8" long. Capacitor body has an oval cross section. Dimensions: 31/32" high x 13/16" deep x 1-7/8" long.
Stock #CAP2407



OIL FILLED CAPACITORS (continued)

MFD	VOLTAGE	MFR. and NO.	LENGTH	WIDTH	HEIGHT*	TERMS.	STOCK NO.
4	660VAC	G.E. #26F1043	2-3/4"	1-5/8"	4-3/8"	Q	CAP9557
4.4	1500VAC	G.E. #23L403	3-1/2"	1-3/4"	6-1/2"	Q	CAP97526
5	330VAC	MALLORY #1466646	2-3/16"	1-5/8"	3-1/4"	Q	CAP9356
5	1000VDC	C.D.E. #SCRN236	2-3/4"	1-5/8"	5"	S	CAP9409
5	2500VDC	G.E. #28F5630	3-5/8"	2"	6-1/2"	S	CAP9559
6	250VAC	G.E. #21L4425	2-3/32"	7/8"	2-1/2"	Wire	CAP9709
6	370VAC	C.D.E. #KKL244	2"	1-1/4"	4"	Q†	CAP2205
6	370VAC	C.D.E. #KKN37U605QP	2"	1-1/8"	3-5/8"	Q	CAP9357
6	370VAC	G.E. #21L3006	2-1/8"	1-3/8"	3-1/4"	Q	CAP95522
6	480VAC	MAGNETEK #VC06048CBTR	2-5/8"	1-7/16"	3-1/4"	Q	CAP97516
6	750VAC	G.E. #23L468	3-1/2"	2"	5"	Q	CAP95523
6.35	330VAC	G.E. #21L415	2-3/16"	1-3/8"	2-5/8"	Solder	CAP9707
7	370VAC	SANGAMO #80A325U73772	2-1/8"	1-5/16"	3-1/2"	Q	CAP2404
7	370VAC	MALLORY #702W09306	2-3/16"	1-3/8"	4-1/4"	Q	CAP2403
7	660VAC	G.E. #26F6624	2-1/8"	1-3/8"	5"	Q	CAP95524
7.1	5000VDC	G.E. #28F2025G11	3-3/4"	2"	9-1/4"	S	CAP9933
7.5	440VAC	MALLORY #10499-01	2-13/16"	2-1/8"	3-7/16"	Q	CAP0835
7.5	480VAC 60HZ	G.E. #72F469	1-7/16"	2-1/2"	4-5/8"	Q	CAP2215
7.7	480VAC	G.E. #21L6000	2-3/4"	1-3/4"	5"	Q	CAP97527
8	660VAC	G.E. #26F6625FA	2"	1-1/8"	6"	Q	CAP2152
8	660VAC	G.E. #26F6654	2-3/4"	1-3/4"	5-3/8"	Q	CAP2153
8	4000VAC	G.E. #28-F2024	3-1/2"	1-7/8"	8-1/2"	S	CAP8802
11.5	1200VDC	G.E. #26F6932	2"	3-1/2"	8-1/2"	Q	CAP20511
12 ±6%	660VAC 60HZ	AEROVOX #N93R6612E23	3"	2"	7-1/4"	Q	CAP2008
12	4900VDC	G.E. #28F2026	4-1/2"	3"	8-1/2"	S	CAP2203
15	300VAC	RONKEN #P71A10156K05	1-1/4"	2"	6"	Q	CAP9301
15	370VAC	RONKEN #P91C12156K05	2-3/4"	1-3/4"	3-1/4"	Q	CAP9361
15	400VAC	AEROVOX #VC150040GBTR	2-5/8"	1-7/16"	4-1/4"	Q	CAP97517
15	660VAC	G.E. #45F634FB	1-7/8"	3-3/4"	6-3/4"	Q	CAP0812
15	660VAC 60HZ	AEROVOX #H64R6615E 28	3"	2"	4-1/4"	Q	CAP2009
15	850VDC	G.E. #97F8653	2"	3-3/4"	8-3/4"	S	CAP20514
15	875VAC 60HZ	CAPTRON #958-423002	4-5/8"	2-7/8"	9-1/4"	S	CAP2105
16	330VAC	MAGNETEK #VC16033CBTR	2-5/8"	1-7/16"	3-1/4"	Q	CAP97518
17.5	330VAC 60HZ	AEROVOX #702W06622	2-7/8"	1-7/8"	5-1/2"	Q	CAP2102 *RF
17.5	440VAC	RONKEN #P91C14186HWR	2-3/4"	1-3/4"	4"	Q	CAP97530
18	660VAC 60HZ	G.E. #26F6629A	1-3/4"	2-3/4"	7-1/2"	Q	CAP2206
19	700VAC 60HZ	CAPTRON #958-442602	4-5/8"	2-7/8"	8-1/2"	S	CAP2106
19.3	480VAC	G.E. #21L6003	3-1/2"	1-3/4"	7-7/8"	Q	CAP97528
20	440VAC 60HZ	G.E. #45F357FB	2"	3"	6-3/8"	Q	CAP2011
20	500VAC	G.E. #21L6230	2"	3-9/16"	7-7/8"	Q	CAP0817
20	660VAC	E.U.C. #952-442503	3"	4-7/8"	6"	Q	CAP9504
20	660VAC 50/60HZ	G.E. #26F6136	1-3/4"	3-1/2"	7-1/2"	Q	CAP2207
22.5	330VAC	G.E. #297F6773	2-3/4"	1-3/4"	4-1/2"	Q	CAP97519
24	660VAC	G.E. #26F6693	3-1/2"	1-3/4"	7-7/8"	Q	CAP97529
24	260VAC	MAGNETEK #VC24017FBTR	2-5/8"	1-7/16"	4"	Q	CAP97520
25	500VAC	G.E. #21L6255	3-5/8"	2"	7-3/4"	Q	CAP95512
25	700VAC 400HZ	G.E. #26F6805-FC	4-1/2"	2-7/8"	9-3/4"	S	CAP9457
25	330VAC	VARIOUS	2-3/4"	1-3/4"	5"	Q	CAP9360
25	600VDC	G.E. #26F5525	1-3/4"	3-1/2"	8-1/4"	S	CAP2208
25	660VAC	MALLORY #38KC6625	1-3/4"	3-1/2"	6"	Q	CAP2051
30	370VAC	MALLORY #C38FD3730	3-3/4"	2"	3-3/8"	Q	CAP20513
30	500VDC	G.E. #26F6910	1-3/4"	3-1/2"	8-1/4"	S	CAP2209
30	600VDC	G.E. #97F8674	1-3/4"	3-1/4"	8-1/4"	S	CAP2210
30	660VAC	G.E. #26F6146	3-1/2"	1-7/8"	8-1/2"	Q	CAP95514
30	800VDC	G.E. #97F8683	4-1/2"	2-3/4"	7-1/2"	S	CAP95528
30	1500Vpk	G.E. #26T6786FC	3-7/8"	4-1/2"	10-3/4"	S	CAP2211
34	240VAC	MAGNETEK #VC34017FBTR	2-5/8"	1-7/16"	4"	Q	CAP97521
35	370VAC	AEROVOX #Z64P3735M31	2-3/4"	1-3/4"	4-1/4"	Q	CAP97532
37.5	800VDC	G.E. #26F609	4-5/8"	2-7/8"	10"	S	CAP9652
37.5	800VAC	E.U.C. #958-502801	4-1/2"	2-7/8"	9"	Q	CAP9307

*S=Screw Q=Quick Disconnect †5/8" long mounting screw on bottom

Continued on next page

CAPACITORS

CAPACITORS

OIL FILLED CAPACITORS (continued)


MFD	VOLTAGE	MFR. and NO.	LENGTH	WIDTH	HEIGHT*TERMS.	STOCK NO.
40	400VAC	C.D.E. #SCRN218	3-5/8"	2"	8-3/4" Q	CAP9108
40	600VAC 60HZ	G.E. #26F6828FC	4-1/2"	2-3/4"	8-1/2" S	CAP2151
45	330VAC 60HZ	DIELEKTROL #26F1507 FA	3-5/8"	2"	7-3/4" Q	CAP9402
47.5	440VAC	ASC #X386S(LU01)	2-5/8"	2-5/8"	4-3/8" Q	CAP2505
50	200VAC	C.D.E. #SCRN210	3-1/2"	2"	7" S	CAP9450
50	440VAC	G.E. #26F1599	4-1/2"	2-7/8"	7-1/4" Q	CAP95516
88	1200VDC	AEROVOX or G.E.	4-5/8"	3-7/8"	10-1/2" S	CAP9311
100	120	G.E. #97F7504	3-5/8"	1-7/8"	4" S	CAP2110
106	1150VDC	AEROVOX #ZR112YW106P01	2-9/16" dia.	5-1/4" high	Q	CAP2303
120	220VAC 60HZ	G.E. #97F3327	2-5/8"	2-5/8"	5-1/4" Q	CAP2202

*S=Screw Q=Quick Disconnect

AXIAL LEAD CAPACITORS

MFD	VOLTAGE	MANUFACTURER	NO.	LENGTH	DIA.	STOCK NO.
33	315VDC	ELNA	CEW 6D	1-3/4"	3/4"	CAP2810
50	100VDC	MALLORY	TT100X50	1-3/4"	3/8"	CAP99511
50	250VDC	MALLORY	677-8735	1-5/8"	3/4"	CAP99512
200	50VDC	MALLORY	TT50X200	1-3/8"	7/16"	CAP99518
450	250VDC	CDE	WBR450-250	3-1/16"	1-3/8"	CAP91533
500	25VDC	SPRAGUE	39D	1-3/16"	7/8"	CAP91523
600	15VDC	SPRAGUE	39D	2-3/16"	1/2"	CAP91519
650	200VDC	MEPCO	3059	3-5/16"	1"	CAP91534
800	40VDC	SPRAGUE	34D	2-3/4"	7/8"	CAP9853
1500	50VDC	SPRAGUE	M39018	3-3/16"	1"	CAP9704
2200	25VDC	MALLORY	20-82701	2-3/4"	7/16"	CAP91524
2200	50VDC	NIPPON CHEM CON	CE02W	2"	1-1/16"	CAP9703
3500	25VDC	MALLORY	20-85110	1-5/8"	1-1/16"	CAP91525
3700	40VDC	MALLORY	113A3243P8	3-5/8"	1-1/16"	CAP91527
5000	50VDC	SPRAGUE	53D	2-5/8"	1"	CAP9455
6400	20VDC	MALLORY	20-52603	2-5/8"	1-1/16"	CAP91520
6800	40VDC	MALLORY	20-85637	3-1/8"	1-1/16"	CAP91528
8000	20VDC	MALLORY	20-86406	2-3/16"	1-1/16"	CAP91521
9500	20VDC	MALLORY	20-52863	3-11/16"	1-1/16"	CAP91522
10000	25VDC	MALLORY	032-18007	3-5/8"	1-1/8"	CAP91526
10000	15VDC	MALLORY	TCG103U015N2L	2-3/4"	1"	CAP9915

HIGH VOLTAGE CAPACITORS



This "door knob" type capacitor has female 8X32 tapped holes at each end for connections. We have them in the following sizes:

PF	MNF. & #	VOLT	DIA.	LN	STOCK NO.	PRICE
2000	TDK, #UHV-9A	40 KVDC	2-1/4"	1-1/16"	HVCAP2001	
2700	TDK, #UHV-6A	30 KVDC	2-1/4"	13/16"	HVCAP2200	

ASC TYPE X637 FILM CAPACITORS

Metalized polyester construction combining a high capacitance with small size. Ideal for motors and other general purpose AC applications. All capacitors in this series have the following specifications: Operating temperature -55° C. to +85° C. at full rated voltage. Rated 220-250 VAC 50/60 Hz. Tolerance ±10%. All capacitors have sturdy 6" long wires for connections.

MFD	Voltage	Dia.	Length	Stock #	Price
3.0	200	5/8"	1-5/16"	CAP9550	
5.0	250	5/8"	1-3/4"	CAP9551	

MOTOR START CAPACITOR

JIC MPP. 25 MFD 240 VAC. 60 Hz. Dimensions: 1-13/16" dia. x 3" long.

Stock #CAP9109



MOTOR STARTING CAPACITOR

MALLORY, #P18910. Rated 189-227 MFD 110 VAC. Has dual 1/4" quick connectors for electrical connections. Dimensions: 1-13/16" dia. x 3-3/8" long.

Stock #CAP97512



POLYPROPYLENE FILM CAPACITOR WESCO #32 MM. Rated 0.47 MFD, ±10%. 400 VDC. Dimensions: 1/2" dia. x 1-1/2" long. Has 2" long axial wire leads.

Stock #CAP2504

OIL FILLED CAPACITOR

ASC #X386S (LU01). 47.5 mfd ±5%. 440 VAC 60 Hz. Housed in a round metal can. Has 1/4" quick connect terminals. Uses SPEARINOL dielectric. Contains no PCB'S. Dimensions: 2-5/8" diameter x 4-3/8" high, including terminals.


Stock #CAP2505



VACUUM VARIABLE CAPACITOR

JENNINGS, #CVA-7-35N91. 3.5-7 PF, 35,000 V. Six #10 1/2" X32 long tpi mounting studs on a 2-3/8" dia. bolt pattern. Adjustment actuator is 1/4" dia. x 1/2" long, flattened one side. Dimensions: 3" dia. x 4-1/2" long.

Stock #VHVCAP9255




Similar to above except JENNINGS, #CVCJ-1000-5S. 7-1000 PF, 5000 V.

Stock #VHVCAP9656

METALIZED POLYESTER CAPACITOR

PANASONIC, #225K-630G. Rated 2.2 MFD ±10%. 630 VDC. Radial leads. Dimensions: 1-3/16" nom. wide x 1" high (excluding leads) x 21/32" deep. Wire leads are 1-1/4" long.

Stock #CAP9858



MOTOR CAPACITOR

SK CAPACITOR Co., #CF505U25TL. The unit is rated 5 MFD +10% -5%. The voltage rating is 250 VAC 50/60 Hz. The capacitor has 3" flexible leadwires. The body of the capacitor is molded plastic. A bracket with a rectangular mounting hole is permanently attached to the body of the capacitor. The mounting hole is approx. 3/16" wide x 7/32" long. Temperature rating is -25°C to +70°C. This is an excellent capacitor for motor starting and running applications. Dimensions: 1-1/2" wide x 1-7/16" high (including bracket) x 19/32" thick.

Stock #CAP2053

